

NUT SPLITTER SERIES



DURABLE,
SAVE TIME AND EFFORT

2436 CHARGING TYPE HYDRAULIC NUT SPLITTER

EBS-2436



EB-2436



DES-2436 (Brushless drive)



DE-2436 (Brushless drive)



TECHNICAL DATA

Max.output:	50KN
Stroke:	18mm
Cutting times: (Per saturation voltage)	250times Depend on M12-4.8 grade nut
Voltage/capacity:	18V/4.0Ah
Net weight:	6.4kg
Charger voltage:	100-240VAC
Charging time:	2 hours
Splitting range:	13-24mm
Thread of nut range:	M8-M24
Package:	Plastic box

ACCESSORIES

Battery:	2pcs
Charger:	1pc



2432 CHARGING TYPE HYDRAULIC NUT SPLITTER

EBS-2432



With continuous function

EB-2432



Regular function

DES-2432 (Brushless drive)



With continuous function

DE-2432 (Brushless drive)



Regular function

TECHNICAL DATA	
Max.output:	50KN
Stroke:	18mm
Cutting times: (Per saturation voltage)	250times Depend on M12-4.8 grade nut
Voltage/capacity:	18V/4.0Ah
Net weight:	6.4kg
Charger voltage:	100-240VAC
Charging time:	2 hours
Splitting range:	13-24mm
Thread of nut range:	M8-M24
Package:	Plastic box
ACCESSORIES	
Battery:	2pcs
Charger:	1pc











MINI CHARGING TYPE HYDRAULIC NUT SPLITTER

GES-24 / GE-24



FEATURES

-  Micro computer control system-automatically detect the pressure when it is crimping, with double safety protect.
-  The hydraulic unit incorporates an automatic retraction which returns the piston into its starting position when the maximum operating pressure is reached.
-  The tool equipped with a double piston pump which characterized by a fast approach towards the connecting material and a slow working stroke.
-  The crimping head can be smoothly turned by 350° around the longitudinal axis in order to gain better access to tight corners and other difficult working areas.
-  If a deviation from the set operation pressure or low battery charges is identified, an acoustic signal sounds and a red display flashes.
-  All tools can be controlled by one trigger. This results in an easy handling and a better grip compared to a two button operation.
-  Li-ion batteries do neither have a memory effect nor self discharge. Even after long periods of non operation the tool is always ready to operate. In addition we see a lower power weight ratio with 50% more capacity and shorter charging cycles compare to NiMH batteries.
-  A Temperature sensor makes the tool stop working automatically when the temperature over 60°C under long time working, the fault signal sounds, it means the tool can't continue work until the temperature reduced to the normal.

TECHNICAL DATA

Max.output:	50KN
Stroke:	18mm
Cutting times: (Per saturation voltage)	250times Depend on M12-4.8 grade nut
Voltage/capacity:	18V/2.0Ah
Net weight:	2.8kg
Charger Voltage:	100-240VAC
Charging time:	2 hours
Splitting range:	13-24mm
Thread of nut range:	M6-M16
Package:	Plastic box

ACCESSORIES

Battery:	2pcs
Charger:	1pc



GES-2432 / GE-2432 Single cutter head

TECHNICAL DATA	
Max.output:	120KN
Stroke:	18mm
Cutting times: (Per saturation voltage)	250times Depend on M12-4.8 grade nut
Voltage/capacity:	18V/2.0Ah
Net weight:	2.8kg
Charger voltage:	100-240VAC
Charging time:	2 hours
Splitting range:	13-24mm
Thread of nut range:	M8-M24
Package:	Plastic box
ACCESSORIES	
Battery:	2pcs
Charger:	1pc



GES-2436 / GE-2436 Double cutter head

TECHNICAL DATA	
Max.output:	120KN
Stroke:	18mm
Cutting times: (Per saturation voltage)	250times Depend on M12-4.8 grade nut
Voltage/capacity:	18V/2.0Ah
Net weight:	2.8kg
Charger voltage:	100-240VAC
Charging time:	2 hours
Splitting range:	13-24mm
Thread of nut range:	M8-M24
Package:	Plastic box
ACCESSORIES	
Battery:	2pcs
Charger:	1pc



MANUAL TYPE HYDRAULIC NUT SPLITTER

CPC-12A (Manual type)



TECHNICAL DATA

Cutting rang:	Φ4-12mm
Output:	45KN
Stroke:	15mm
Length:	315mm
Weight:	1.9kg
Package:	plastic box
Weight of case:	0.56kg

CPC-16A (Manual type)



TECHNICAL DATA

Cutting rang:	Φ4-16mm
Output:	60KN
Stroke:	18mm
Length:	410mm
Weight:	3.4kg
Package:	plastic box
Weight of case:	0.9kg

CPC-22A (Manual type)



TECHNICAL DATA

Cutting rang:	Φ4-22mm
Output:	100KN
Stroke:	24mm
Length:	480mm
Weight:	4.2kg
Package:	plastic box
Weight of case:	1.2kg

YP-24A (Manual type)



TECHNICAL DATA

Max cutting force:	70KN
Stroke:	20mm
Length:	470mm
Weight:	3.5kg
Package:	plastic box
Weight of box:	2.0kg
Size of nut:	M8-M16

YP-24 (Manual type) With safety system inside



TECHNICAL DATA

Max cutting force:	100KN
Stroke:	20mm
Length:	490mm
Weight:	4.0kg
Package:	plastic box
Weight of box:	3.5kg
Size of nut:	M8-M16